

SIMIX Standard-Stirnrad-Getrieberührwerke

TYP SRGMK....	Lieferbare feste Abtriebsdrehzahlen	Ø Rührwelle x max. Länge	Ø x L Kupplung	Propeller Ø*	Flansch Ø**	Gewicht bei max. Wellenlänge
0,12KW-63/4	25/28/32/40/46/50/60 69/81/91/105/118/148/ 163/179/213/250/291/ 309/342/375/447/523/608	20 x 900mm	30 x 80mm	250mm 250mm 200mm 175mm	120mm	15 KG
0,25KW-71/4	46/50/60/69/81/91/105/ 118/148/163/179/213/ 250/291/309/342/375/ 447/523/608	20 x 1100mm	30 x 80mm	300mm 250mm 225mm 200mm	160mm	20 KG
0,37KW-71/	69/81/105/118/148/ 163/179/213/250/291/ 309/342/375/ 447/523/608	20 x 1100mm	30 x 80mm	300mm 275mm 250mm 225mm	160mm	21 KG
0,75KW-80/4	83/95/107/120/134/ 150/165/181/197/214/233/ 251/271/291/313/327/392/ 426/462/498/538	20 x 1100mm	30 x 80mm	350mm 300mm 275mm 250mm	160mm	25 KG
V0,75KW-80/4	66/87/98/108/120/133/146/ 159/174/188/204/213/221/ 241/272/303/336/370/407/ 444/484/526	25 x 1600mm	40 x 120mm	400mm 300mm 275mm 250mm	160mm	30 KG
1,1KW-90/4	107/120/134/ 150/165/181/197/214/233/ 251/271/291/313/327/392/ 426/462/498/538	20 x 1100mm	30 x 80mm	400mm 350mm 300mm 275mm	160mm	31 KG
V1,1KW-90/4	108/120/133/146/ 159/174/188/204/213/221/ 241/272/303/336/370/407/ 444/484/526	25 x 1600mm	40 x 120mm	500mm 400mm 350mm 300mm	160mm	35 KG
1,5KW-90/4	150/165/181/197/214/ 251/271/291/313/327/392/ 426/462/498/538	20 x 1100mm	30 x 80mm	350mm 300mm 275mm	160mm	34 KG
V1,5KW-90/4	146/159/174/188/204/213/ 241/272/303/336/370/407/ 444/484/526	25 x 1600mm	40 x 120mm	500mm 400mm 350mm	160mm	38 KG

Erläuterungen zu Standard-Getriebe-Rührwerken

Standardgetriebe mit Drehstrommotor, Bauform V1; Flanschausführung

Spannung 230/400V, 50/60 Hz, IP55, Iso Kl. F, IE2

(Sonderausführungen und andere Werkstoffe, sowie Rührorgane o. Ä. bieten wir Ihnen auf Anfrage gerne an)